



Certificate of Conformity of the Factory Production Control

No.: 2737-CPR-21-PC-0259-TAT-0142

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Hot finished structural hollow sections (Seamless Pipes) Material: S235JRH, S275 JOH, S275J2H, S355JOH, S355J2H, S355K2H Diameter: 114 mm to 219 mm Wall thickness: 5 mm to 22 mm

placed on the market under the name or trademark of

BAKU STEEL COMPANY CJSC

15 Mir-Jalal, AZ1029 Baku, AZERBAIJAN

and produced in the manufacturing plant (s)

BAKU STEEL COMPANY CJSC, AZER PIPE PLANTS

1 Sulh Street, AZ5000 Sumgait, AZERBAIJAN

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 10210-1:2006

under system 2+ are applied and that

the factory production control is assessed to be in conformity with the applicable requirements.

This certificate was first issued on **19.05.2021**, and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.

The certificate validity will expire on 18.05.2024

İstanbul, **24.05.2023** Date & Place of Issue



Vervielfaitigung nur mit Erlaubnis des TÜV AUSTRIA I The reproduction of this document is subject to the approval by TÜV AUSTRIA www.hvv.al





Certificate of Conformity of the Factory Production Control

No.: 2737-CPR-21-PC-0259-TAT-0142

Annex 1 – Hot finished structural hollow sections (Seamless Pipes)

Intended uses; To be used in metal structures or in composite metal and concrete structures.

Controlled Performance Characteristics;

- Surface Condition and Dimensions,

- Chemical composition
- Yield Strength,
- Elongation,
- Tensile Strength,
- Impact resistance (J2 and K2),
- Weldability
- Non-destructive testing of welds

Steel Grade	Section	Dimensions
S235JRH	Hot finished structural hollow sections	Diameter: 114 mm to 219 mm Wall thickness: 5 mm to 22 mm
S275J0H		
S275J2H		
S355J0H		
S355J2H		
S460MH		

Istanbul, **24.05.2023** Date & Place of Issue



vervielfaltigung nur mit Erfaubris des TÜV AUSTRIA I The reproduction of this document is subject to the approval by TÜV AUSTRIA www.luv.at

CRT-CPR-002b / Rev. No / Date: 03 / 09 03 2020